



Screwless Connectors Luminaire Connectors

LK 980-01/ 3 SK BD N PE L

terminal block, 3 pole, insulating material: PA 6.6, fixing: screw, PE terminal: SK, printing: N ⊕ L, voltage rating: 450 V, current rating: 24.0 A, cross-section rating: 2.5 mm²



Order Info

reference number (ref. no.)	21756
PU	500
EAN	4028012112890

Type

type	terminal block
number of poles	3 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm ²
connection type	screwless
printing	N ⊕ L

Technical Data

voltage rating	450 V
current rating	24.0 A
insulating material	PA 6.6
contact material	Spring Steel, Copper
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
stripping length	8.0-9.0 mm
internal core cross-section max.	1.5 / 2.5 mm ²
external core cross-section min.	0.5 mm ²
external core cross-section max.	2.5 mm ²
fixing	screw
internal core cross-section min.	0.5 mm ²
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes
PE terminal	SK

Approvals

acc. to EN 60998

[Download PDF](#)

acc. to UL

[Download PDF](#)

Accessories

WKZ 980-01

999041

ZEL 110

196420

ZEL 900

196423